

Material Safety Data Sheet – MR⁶⁴Dsinfo



Risk Prevention Systems

3305 Rutherford Road
Suite J
Taylors, SC 29687



MATERIAL SAFETY DATA SHEET – MR⁶⁴ Dsinfo

Section 1: Product & Company Identification

Trade Name: MR⁶⁴ Dsinfo
EPA Number: 10324-169-85441
Product Class: Quaternary Ammonium Compound
Product Use: Treated Article Mold Remediation
Manufacturer: Risk Prevention Systems
3305 Rutherford Road
Suite J
Taylors, SC 29687
Telephone Numbers: 24 hr. Emergency Assistance: 1-888-328-6653 (Mon – Fri)
Product or Company Information: 1-888-328-6653 (Mon – Fri)

Section 2: Composition/Information on Ingredients

Ingredient	CAS #	Wt. %
Alkyl dimethyl benzyl ammonium chloride (C ₁₂₋₁₆)	68424-85-1	2.20
Octyl decyl dimethyl ammonium chloride	32426-11-2	1.65
Diocetyl dimethyl ammonium chloride	5538-94-3	0.825
Didecyl dimethyl ammonium chloride	7173-51-5	0.825

Section 3: Hazards Identification

Emergency Overview Clear, colorless to straw colored liquid. Corrosive to the eyes, skin, gastrointestinal tract, and respiratory system.

Potential Health Effects:

- Skin:** Causes corrosive burns. Brief exposures may cause irritation and defatting of the skin. Exposures not promptly washed off may lead to toxic effects similar to ingestion. Harmful if absorbed through skin.
- Eyes:** Causes burns and may result in permanent injury to eyes including blindness.
- Inhalation:** Mists and vapors can irritate the throat and respiratory tract. High vapor concentrations may cause central nervous system effects. Symptoms may include headaches, dizziness, and drowsiness. Harmful if inhaled.
- Ingestion:** Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea and possibly death. Harmful if swallowed.
- Chronic:** Ingestion of ethanol by pregnant women can cause reproductive toxicity to the fetus.

Section 4: First Aid Measures

- Eyes:** Immediately flush eyes with water for 15-20 minutes, while holding eyelids open. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Seek medical attention at once.
- Skin or Clothing:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

Material Safety Data Sheet – MR⁶⁴Dsinfo

- Inhalation:** If symptoms are experienced, move victim to fresh air. If person is not breathing call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or doctor for further treatment advice.
- Ingestion:** Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.
- Note to Physician:** Probable mucosal damage may contraindicate the use of gastric lavage.

Section 5: Fire Fighting Measures

- Flash Point:** Over 201°F (over 94°C)
- Upper & Lower Flame Limits** Not determined
- Extinguishing Media:** Dry chemical, foam, carbon dioxide or water fog. Solid water streams may spread burning liquid.
- Fire Fighting Equipment & Instructions:** Firefighters should wear full protective clothing including self-contained breathing apparatus. Cool fire exposed containers with spray.
- Hazardous Combustion Products:** Irritating and toxic gases or fumes may be released during a fire.

Section 6: Accidental Release Measures

Spill and Leak Procedures

- Emergency Action:** Isolate spill or leak area immediately. Keep unauthorized personnel away. Stay upwind. Keep out of low areas where vapors may accumulate. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Spill Cleanup:** Ventilate closed spaces before entering. All equipment used when handling the product must be grounded. Floor will be slippery. Do not touch or walk through spilled material. Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Prevent entry into waterways, sewers, basements or confined areas. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material.
- Large Spills:** Dike far ahead of liquid spill for later disposal. Water spray may reduce vapor but will increase foaming. Water may not prevent ignition in closed spaces.

Section 7: Handling & Storage

- Handling Procedures:** Avoid contact with skin and eyes. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Wash thoroughly after work using soap and water.
- Storage Procedures:** Keep the container tightly closed and in a cool, well-ventilated place. Keep from freezing. Do not handle or store near an open flame, heat or other sources of ignition. Prevent electrostatic charge buildup by using common bonding and grounding techniques.

Section 8: Exposure Controls/Personal Protection

- Engineering Controls:** Provide adequate local exhaust ventilation (explosion proof) to maintain worker exposure below exposure limits.

Personal Protective Equipment:

- Eyes/Face:** Wear chemical goggles. Use a face shield if splashing is possible.
- Skin:** Use impervious gloves (rubber or neoprene). Wear suitable protective clothing.

Material Safety Data Sheet – MR⁶⁴Dsinfo

- Respiratory:** If exposure limits are exceeded or if irritation is experienced, an organic-vapor removing cartridge with a pre-filter respiratory (MSHA/NIOSH approved) protection should be worn. Ventilation and other forms of engineering controls are often the preferred means for controlling chemical exposures. Respiratory protection may be needed for non-routine or emergency situations.
- General:** Eye wash fountain and emergency showers are recommended.

The following ingredients have established exposure guidelines:

Ingredient	Exposure Guideline	Guideline Value
Ethanol 64-17-5	ACGIH TWA (2002)	1000 ppm (TWA)
	NIOSH Pocket Guide	1000 ppm (TWA)
	Alberta (Canada)	1000 ppm (TWA), 1250 ppm (STEL)
	British Columbia, Manitoba, New Brunswick, Ontario, Quebec (Canada)	1000 ppm (TWA)
	Saskatchewan (Canada)	1880 mg/m ³ (TWA), 2350 mg/m ³ (STEL)
	Yukon (Canada)	1000 ppm (TWA), 1000 ppm (STEL)
	Mexico – Instruction No. 10	1000 ppm (TWA)

All TWAs are for an 8-hour period and all STELs are for 15 minutes unless specifically noted as being for another time period.

Section 9: Physical & Chemical Properties

- Flash Point:** Over 201°F (over 94°C)
- Specific Gravity:** 1.01 @ 23 °C
- Percent Volatiles:** ND
- Vapor Pressure:** ND
- VOC Content** ND
- Vapor Density:** ND
- Viscosity:** 21.72 cs @24°C
- Evaporation Rate:** ND (Butyl Acetate = 1)
- Pour Point:** ND
- pH :** 11 - 13
- Appearance and Odor:** Clear, colorless to straw colored liquid with benzaldehyde (organic) odor.

Section 10: Stability & Reactivity

- Chemical Stability:** Material is stable.
- Conditions to Avoid:** Keep away from heat and strong oxidizing agents.
- Incompatibilities:** Strong oxidizing agents (may result in fire.), reducing agents
- Hazardous Decomposition:** Carbon monoxide, carbon dioxide and toxic hydrogen chloride vapors.
- Hazardous Polymerization:** Will not occur.

Section 11: Toxicological Information

- Carcinogenicity** No Carcinogenicity data available for this product.
- Acute Oral LD50** 272 mg/kg in rats
- Acute Dermal** Greater than 2g/kg body weight
- Primary Skin** Corrosive –Tox. Category I for dermal effect
- Primary Eye** Corrosive –Tox. Category I

Material Safety Data Sheet – MR⁶⁴Dsinfo

Chemicals Ingredients Listed as Potential or Known Carcinogens

Ingredient	OSHA	NTP	IARC
No ingredients listed in this section.			

Section 12: Ecological Information

Ecotoxicity Very Toxic to aquatic organisms
 Information available upon request. Please contact Mason Chemical Company Technical Service Department.

Environmental Fate
 This product is biodegradable

Section 13: Disposal Considerations

Disposal Instructions

This substance, when discarded or disposed of, is a characteristic hazardous waste according to Federal regulation (40 CFR 261) and is assigned the EPA Hazardous Waste Number of D001. The discarding or disposal of this material must be done at a properly permitted facility in accordance with the regulations of 40 CFR 262, 263, 264, and 268. Additionally, the discarding or disposal of this material may be further regulated by state, regional, or local regulations. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this MSDS incomplete, inaccurate or otherwise inappropriate.

The transportation, storage, treatment and disposal of this waste material must be conducted in compliance with all applicable Federal, state, and local regulations.

Section 14: Transport Information

DOT Hazard Class 8 Corrosive
DOT Proper Shipping Name Disinfectant Liquid Corrosive (Quaternary Ammonium Compound), 8, UN1903, PG III

Section 15: Regulatory Information

TSCA Status

While all ingredients are listed on the TSCA Chemical Inventory, this product is regulated as a pesticide under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA) and not subject to the TSCA Inventory rules for FIFRA uses.

Other Chemical Inventories

All components of this product are listed on the following inventories: Canada (DSL), European Union, China, Korean and Philippines. One or more ingredients are not listed on the following inventories: Australia and Japan.

CERCL/SARA

SARA Title III, Sections 311/312 – This act requires reporting under the Community Right-to-Know provisions due to the inclusion of the following components of this material in one or more of the five hazard categories listed in the 40 CFR 370:

Classification of this product: Immediate, Fire

SARA Title 313 – This act requires submission of annual reports of releases of the following components of this material if the threshold reporting quantities, as listed in 40 CFR 372, are met or exceeded:

Chemical Name	CAS No.	Maximum Concentration	Comment
No ingredients listed in this section.			

Reportable Quantities/Threshold Planning Quantities: CERCLA requires notification of the National Response Center (Telephone 1-800-424-8802) in the event of a release of quantities of the following hazardous materials contained in this product, if the release is equal to or greater than the Reportable Quantities (RQs). SARA 302/304 requires emergency planning, including agency notification, for possible release of the following components of this material, based upon the Threshold Planning Quantities (TPQs) and/or release of Reportable Quantities.

Chemical Name	Reportable Quantity (RQ)	Threshold Planning Quantity (TPQ)
No ingredients listed in this section.		

Material Safety Data Sheet – MR⁶⁴Dsinfo

State & Provincial Right to Know & Selected Regulatory Lists

The following ingredients appear on various state right to know lists and/or California's Proposition 65 List

Chemical Name	State List
Ethanol	AZ, CA, CT, FL, ID, MA, MN, NJ, PA, RI
Benzyl Chloride (trace impurity < 10ppm)	AZ, CA, CAP65C, FL, IL, MA, MN, NJ, PA

AZ – Arizona Ambient Air Quality Guidelines

CT – Connecticut Hazardous Air Pollutants

CA – California Director's List of Hazardous Substances

CAP65C – California Prop 65 Carcinogen

FL – Florida Substances List

ID – Idaho Non-carcinogen Toxic Air Pollutants

IL – Illinois Toxic Air Contaminant - Carcinogenic

MA – Massachusetts Right to Know List

MN – Minnesota Hazardous Substances List

NJ – New Jersey Right to Know List

PA – Pennsylvania Right to Know List

RI – Rhode Island Hazardous Substances List

WHMIS Classification: B3, E, D1B. This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Section 16: Other Information

Current Issue Date: November 2008

Previous Issue Date: NONE

Changes from Previous Issue Date: New

Hazard Ratings	HMIS	NFPA
Health	3	3
Flammability	2	2
Reactivity	0	0
PPE	X	

Disclaimer

Disclaimer: Nothing contained herein grants or extends a license, express or implied, in connection with patents, issued or pending, of the manufacturer or others. The information contained herein is based on the manufacturer's own study and the works of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. The manufacturer shall not be held liable (regardless of fault) to the vendee's employees, or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information.

The seller makes no warranty expressed or implied concerning the accuracy or any results to be obtained from the use of any information and no warranty expressed or implied concerning the use of the products. The buyer assumes all risks of the use and/or handling.